

PRESSALIT.

Toilet seat Colani with cover With stabilizing buffers and universal hinge (B83).

R36000-B83999 Item number

EAN:5708590070650

NBS:N13:300


Toilet seat, Colani, with stabilizing buffers, with cover,


incl. universal hinge with 3" bolt.


Color White

Description Toilet seat, Colani, with stabilizing buffers, with cover,

incl. universal hinge with 3" bolt.







Seat/cover: Thermoset plastic (urea) **Materials**

Strap: Stainless steel V2A

Product capacity This product has been tested statically up to 825 lbs. As the European standard for technical aids for disabled, EN 12182:2012, requires a static test with safety factor 1.5,

the nominal maximum load for this product is therefore 550 lbs.

Weight 3,703 kg

Carton size 490x389x84 mm

Gross weight 4,103 kg

Weight per crate 20,515 kg

5 Qty per crate

12 Crates per pallet

Qty per pallet 60



PRESSALIT.

Toilet seat Colani with cover With stabilizing buffers and universal hinge (B83).

Cleaning

Use a mild soap solution to clean the toilet seat. Please take care that the seat and hinges are not left damp. For disinfecting the seat, e.g. ethanol 85% can be used. Make sure that the product is wiped down with a soft rag wrung out in clear water and dried off with a soft, dry cloth immediately after disinfection.

| Avoid contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make sure that the seat and cover are kept in an upright position until all cleaning agent has been flushed away.

Warranty

Your Pressalit toilet seat is subject to a 10-year product warranty against presentation of receipt. You should contact the dealer or store where you purchased the seat in the event of a complaint.

| Strict | Stri

Subject to changes in the product range, technical changes and printing errors.

pressalit.com

Pressalit A/S Pressalitvej 1 DK-8680 Ry Tel.: +45 8788 8788 Fax: +45 8788 8789 E-mail: pressalit@pressalit.com

PRESSALIT®