

PRESSALIT.

Toilet seat Dania with cover With stabilizing buffers and universal hinge (B83).

Item number R37000-B83999

EAN:5708590070674

NBS:N13:300


Toilet seat, Dania, with stabilizing buffers, with cover,


incl. universal hinge with 3" bolt.


Color White

Description Toilet seat, Dania, with stabilizing buffers, with cover,

incl. universal hinge with 3" bolt.







Materials Seat/cover: Thermoset plastic (urea)

Strap: Stainless steel V2A

Product capacity

This product has been tested statically up to 825 lbs. As the European standard for

technical aids for disabled, EN 12182:2012, requires a static test with safety factor 1.5,

the nominal maximum load for this product is therefore 550 lbs.

Weight 3,69 kg

Carton size 457x389x68 mm

Gross weight 4,19 kg

Weight per crate 20,95 kg

Qty per crate 5

Crates per pallet 18

Qty per pallet 90



PRESSALIT.

Toilet seat Dania with cover With stabilizing buffers and universal hinge (B83).

Cleaning

Use a mild soap solution to clean the toilet seat. Please take care that the seat and hinges are not left damp. For disinfecting the seat, e.g. ethanol 85% can be used. Make sure that the product is wiped down with a soft rag wrung out in clear water and dried off with a soft, dry cloth immediately after disinfection.

| Avoid contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make sure that the seat and cover are kept in an upright position until all cleaning agent has been flushed away.

Warranty

Your Pressalit toilet seat is subject to a 10-year product warranty against presentation of receipt. You should contact the dealer or store where you purchased the seat in the event of a complaint.

| Strict | Stri

Subject to changes in the product range, technical changes and printing errors.

pressalit.com

Pressalit A/S Pressalitvej 1 DK-8680 Ry Tel.: +45 8788 8788 Fax: +45 8788 8789 E-mail: pressalit@pressalit.com

PRESSALIT®