

PRESSALIT.

Toilet seat Dania with open front, with cover With stabilising buffers and extra strong cross-bar hinge (D92).

MaterialsSeat/cover: Thermoset plastic (urea) Strap: Stainless steel V2AProduct capacityThis product has been tested statically up to 375 kg. As the European standard for technical aids for disabled, BS/EN 12182:2012, requires a static test with safety factor 1.5, the nominal maximum load for this product is therefore 250 kg.Weight3,557 kgCarton size457x389x68 mmGross weight3,957 kgQty per crate5519,785 kgQty per pallet18Qty per pallet90	Item number Colour Description	R38000-D92999 VVS:615657000 NRF:6190614 EAN:5708590316000 HMI: 1848 NBS:N13:300 Toilet seat, Dania, with stabilising buffers, open front, with cover, incl. extra strong cross-bar hinge. White Toilet seat, Dania, with stabilising buffers, open front, with cover, incl. extra strong cross-bar hinge.
MaterialsStrap: Stainless steel V2AProduct capacityThis product has been tested statically up to 375 kg. As the European standard for technical aids for disabled, BS/EN 12182:2012, requires a static test with safety factor 1.5, the nominal maximum load for this product is therefore 250 kg.Weight3,557 kgCarton size457x389x68 mmGross weight3,957 kgWeight per crate19,785 kgQty per crate5Crates per pallet18		405 - 452 - 452 - 75 - 452 - 75 - 452 - 47153 - 47156 - 47050 -
Product capacityThis product has been tested statically up to 375 kg. As the European standard for technical aids for disabled, BS/EN 12182:2012, requires a static test with safety factor 1.5, the nominal maximum load for this product is therefore 250 kg.Weight3,557 kgCarton size457x389x68 mmGross weight3,957 kgWeight per crate19,785 kgQty per crate5Crates per pallet18	Materials	Seat/cover: Thermoset plastic (urea)
Carton size457x389x68 mmGross weight3,957 kgWeight per crate19,785 kgQty per crate5Crates per pallet18	Product capacity	This product has been tested statically up to 375 kg. As the European standard for technical aids for disabled, BS/EN 12182:2012, requires a static test with safety factor
Gross weight3,957 kgWeight per crate19,785 kgQty per crate5Crates per pallet18	Weight	3,557 kg
Weight per crate19,785 kgQty per crate5Crates per pallet18	Carton size	457x389x68 mm
Qty per crate5Crates per pallet18	Gross weight	3,957 kg
Crates per pallet 18	Weight per crate	19,785 kg
	Qty per crate	5
Qty per pallet 90	Crates per pallet	18
	Qty per pallet	90



Toilet seat Dania with open front, with cover With stabilising buffers and extra strong cross-bar hinge (D92).

Cleaning Use a mild soap solution to clean the toilet seat. Please take care that the seat and hinges are not left damp. For disinfecting the seat, e.g. ethanol 85% can be used. Make sure that the product is wiped down with a soft rag wrung out in clear water and dried off with a soft, dry cloth immediately after disinfection.
<i>Avoid contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make sure that the seat and cover are kept in an upright position until all cleaning agent has been flushed away.</i> Warranty Your Pressalit toilet seat is subject to a 10-year product warranty against presentation of receipt. You should contact the dealer or store where you purchased the seat in the event of a complaint.
br>
br>In the event of complaints about defective materials and/or manufacturing defects and/or functional limitations ascertained within a 10-year period, following proper use and cleaning of the toilet seat (we reserve the right to examine the toilet seat at our factory), Pressalit will deliver spare parts or replace the toilet seat by an identical or similar model. If the color is no longer available, Pressalit reserves its right to replace the toilet seat by a similar model in the color white. Upon replacement or delivery of a spare part, the warranty period will not be extended nor renewed. If replacement is not possible, Pressalit may instead refund the purchase price. Subject to changes in the product range, technical changes and printing errors.

pressalit.com

Pressalit A/S Pressalitvej 1 DK-8680 Ry Tel.: +45 8788 8788 Fax: +45 8788 8789 E-mail: pressalit@pressalit.com

