



# PRESSALIT®

## Pressalit Plan 780

Toilet seat with soft close and lift-off incl. combi hinge in stainless steel

### Features

Lift-off, Soft close

### Item number

780000-D98999  
NRF:6190226  
EAN:5708590319728

Pressalit Plan stands for perfect fit and has a stunning square design with soft close and lift-off. Specially designed for Keramag Renova No.1 Plan.




### Colour

White

### Description

PRESSALIT toilet seat with cover, model "Pressalit Plan", art. no. 780 made of colour ingrained duroplast with D98 fixed hinge of stainless steel and plastic.

- centre distance: 155 mm
- load - ring seat 240 kg
- suitable for Keramag Renova Nr. 1 Plan
- 10 year guarantee



### Design type

Wrap-over

### Designer

Pressalit

### Design year

2012



---

**Pressalit Plan 780****Toilet seat with soft close and lift-off incl. combi hinge in stainless steel**

---

**Materials****TOILET SEAT:**

The material is colour ingrained duroplast (UF A 10 = urea formaldehyde) that contains no environmentally hazardous substances. UF plastic comprises 67% urea formaldehyde resin, 28% cellulose, as well as 5% minerals, pigments, lubricants and moisture content. The raw material from the supplier contains up to 0.03% free formaldehyde and even less following curing.

**BUFFERS:**

EVA (copolymer made of ethylene and vinyl acetate).

**DAMPER KIT (only relevant for toilet seats with soft close):**

Hydraulic damper with stainless steel damper casing and thermoplastic parts.

**MOUNT/HINGES:**

Stainless steel model W. no. 1.4301/M and thermoplastic.

**Product capacity**

Load - ring seat 180 kg

**Weight**

2,591 kg

**Carton size**

488x388x72 mm

**Gross weight**

2,951 kg

**Crate size**

500x400x368 mm

**Weight per crate**

14,755 kg

**Qty per crate**

5

**Crates per pallet**

18

**Qty per pallet**

90

**Cleaning**

Use a mild soap solution to clean the seat. Please take care that the seat and hinges are not left damp. Dry off any residual water or cleaning agent with a soft cloth. Avoid contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make sure that the seat and cover are kept in an upright position until all cleaning agent has been flushed away.



# PRESSALIT®

---

**Pressalit Plan 780****Toilet seat with soft close and lift-off incl. combi hinge in stainless steel**

---

**Warranty**

Your Pressalit toilet seat is subject to a 10-year product warranty against presentation of receipt. You should contact the dealer or store where you purchased the seat in the event of a complaint. In the event of complaints about defective materials and/or manufacturing defects and/or functional limitations ascertained within a 10-year period, following proper use and cleaning of the toilet seat (we reserve the right to examine the toilet seat at our factory), Pressalit will deliver spare parts or replace the toilet seat by an identical or similar model. If the color is no longer available, Pressalit reserves its right to replace the toilet seat by a similar model in the color white. Upon replacement or delivery of a spare part, the warranty period will not be extended nor renewed. If replacement is not possible, Pressalit may instead refund the purchase price.

Subject to changes in the product range, technical changes and printing errors.

---

[pressalit.com](http://pressalit.com)

---

PRESSALIT®