




PRESSALIT®

Product Item number	Changing table, 800 x 900 mm, electrically height adjustable R8661000
Colour	VVS:777636010 NRF:7501974 EAN:5708590338354 HMI: 100176 White
Product description	 <p>Pressalit offers a wide range of daycare changing tables, both free-standing and wall-hung, in several sizes and models. The wall-hung tables are also available in versions where the worktop folds away, which are suitable for rooms with limited space. Of particular use to daycare facilities and kindergartens are the low start wall-hung changing tables, which can be lowered to a height that allows children to climb onto the worktop themselves.</p> <p>All types of daycare changing tables are available in versions with sanitary appliances and a choice of taps, with or without pull-out shower heads.</p> <p>Low start, wallhung changing table, 800 x 900 mm. With electric motor and transformer, height adjustable from 300 mm - 1000 mm, with wired hand control and safety stop function. Molded worktop, incl. 2 wire baskets. Materials: ABS plastics, synthetic acrylic and powder-lacquered steel. Excl. mounting kit.</p>
Adjustability Adjustment height Product capacity Speed upwards Noise level	Height adjustable 700 mm Max load: 75 kg. Speed up mm: 38 mm/s Speed down mm: 38 mm/s 48 dB
Materials	Lifting unit and baskets: Powder-laquered steel. Worktop: ABS with acrylic.



Product	Changing table, 800 x 900 mm, electrically height adjustable
Item number	R8661000
Ergonomy	<p>The smooth height adjustment ensures that it is always possible to set the table at an ergonomically correct height.</p> <p>The table descends to a very low position, which offers the advantage that toddlers can easily climb up and down themselves.</p> <p>Thereby unnecessary lifting is avoided.</p>
Features	<p>Easy-to-clean surfaces ensure optimum hygiene.</p> <p>Integrated safety system prevents entrapment.</p>
Mains connection (V)	230
Actuator (motor)	LA31 Deskline (Linak), 2500N, IPX1
Control box	CBD6 (Linak), IP20
Wired remote control	HB30 (Linak), IPX4
Power consumption (maximum load)	<p>Power consumption by maximum load, watt: 96 W</p> <p>Power consumption by standby: 0,1 W</p>
Warranty	<p>Pressalit makes a commitment to remedy material and manufacturing defects for a period of three years from the invoicing date.</p>
Cleaning	<p>Changing table.</p> <p>The product is to be cleaned with hot water or a mild soapy cleaning agent.</p> <p>Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged.</p> <p>The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container.</p> <p>DISINFECTANTS:</p> <p>Clinimax Difficil-S</p> <p>Erisan OXY+</p> <p>NON-DISINFECTANTS:</p> <p>Suma Star free D1</p> <p>Taski 100</p> <p>Taski 200</p> <p>The product must be wiped down with a soft rag wrung out in clear water immediately after cleaning, as some materials may otherwise be discolored and stained, and the surface coating may deteriorate.</p>



PRESSALIT®

Product	Changing table, 800 x 900 mm, electrically height adjustable
Item number	R8661000
Declaration of conformity	<p>CE UK MASK-ROHS This product complies with the relevant requirements of:</p> <ul style="list-style-type: none">- Council Directive 2006/42/EC on machinery- Council Directive 2011/65/EC on RoHS. <p>For the UK: - The Supply of Machinery (Safety) Regulations 2008</p> <ul style="list-style-type: none">- Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012



PRESSALIT®

Product	Changing table, 800 x 900 mm, electrically height adjustable
Item number	R8661000

Installation in different wall types

	<p>Concrete >B25</p> <p>V8608 - Mounting kit, 6 coach screws Ø10 x 70 - plugs SX12. To be ordered separately.</p>	
	<p>Solid Brick >= Mz12</p> <p>V8608 - Mounting kit, 6 coach screws Ø10 x 70 - plugs SX12. To be ordered separately.</p>	
	<p>Solid Sand Lime Brick >= Hlz12</p> <p>V8608 - Mounting kit, 6 coach screws Ø10 x 70 - plugs SX12. To be ordered separately.</p>	
	<p>Aerated Concrete P4</p> <p>V8658 - Mounting kit, 6 coach screws Ø10 x 70 - plugs GB14. To be ordered separately.</p>	
	<p>Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood</p> <p>V8608 - Mounting kit, 6 coach screws Ø10 x 70 - plugs SX12. NB! Plugs are not needed. To be ordered separately.</p>	



PRESSALIT®

Product Item number	Changing table, 800 x 900 mm, electrically height adjustable R8661000
	<p>Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood</p> <p>Wall fasteners (6 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.</p>
	<p>Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (2 mm)</p> <p>Wall fasteners (6 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.</p>
	<p>Drywall (2 x 12,5 mm) water-resistant</p> <p>Mounting in this wall type is not recommended - risk of fatal injury to persons and walls.</p>

pressalit.com