

## PRESSALIT.

Dreduct	MATRIX ANCLE DEEP wash basin without overflow, left facing
Product	MATRIX ANGLE DEEP wash basin without overflow, left-facing
Item number	R2143112000
	VVS:639871000
	EAN:5708590340845
	HMI: 138168
Colour	White
Product description	MATRIX is a series of wash basins, most of them are designed by Pressalit. MATRIX SMALL and CURVE wash basins fit onto PLUS, SELECT and VALUE was basin brackets, whereas MATRIX MEDIUM, ANGLE, ANGLE DEEP and SQUARE are tailor made to fit specific brackets.
	MATRIX ANGLE DEEP vanity wash basin, 1000 x 571 x 158 mm, left-facing, with tw integrated anthracite handrails in the front, with tap hole Ø36 mm, without overflow. Supplied with drain fitting. The wash basin has raised edges, preventing water from running over the back or down the outer sides. Materials: Cultured marble with a high-polished, pore-free sanitary gel coating. Suitable for mounting on MATRIX basin unit (R4842 (UK R4847), R2011).
Product capacity	200 kg.
Materials	Cultured marble with a high-polished, pore-free sanitary gel coating.
Warranty	Pressalit makes a commitment to remedy material and manufacturing defects for a period of five years from the invoicing date.
Cleaning	<ul> <li>For cleaning the wash basin, use hot water and a mild soapy cleaning agent. Make sure that the product is wiped down with a soft rag wrung out in clear water immediately after cleaning.</li> <li>For disinfecting the wash basin, the following agents can be used: Sodium hydroxide 5%</li> <li>Acetic acid solution 10%</li> <li>Ethanol solution 70%</li> <li>Sodium hypochlorite 5%, active chlorine</li> <li>Sodium chloride 170g/l, diluted to 50%.</li> <li>Make sure that the product is wiped down with a soft rag wrung out in clear water immediately after disinfection.</li> <li>NB! Do not use abrasive cleaning agents, as this will cause damage to the surface of the wash basin.</li> </ul>



## PRESSALIT.

Product	MATRIX ANGLE DEEP wash basin without overflow, left-facing
Item number	R2143112000
Declaration of conformity	Declaration of Performance         Compliance criteria according to EN 14688:2015.         4.1 Load resistance: stable, without cracks or deformations.         4.2 Draining of water: Water drained away completely.         4.3 Resistance to temperature changes: Without cracks, delaminations.         4.4 Resistance to chemicals and staining agents:         - Sodium hydroxide 5% - without staining or deterioration;         - Acetic acid solution 10% - without staining or deterioration;         - Ethanol sol. 70% - without staining or deterioration;         - Sodium hypochlorite 5% active chlorine - without staining or deterioration;         - Sodium chloride 170g/l diluted to 50% - without staining or deterioration.         4.5 Surface stability / resistance to scratching: Do not use abrasives on the surface         4.6 Cleanability: Smooth, non-absorbant surfaces.         4.7 Protection against overflowing: CL 00.         4.8 Durability: Product is considered durable.

## pressalit.com

Pressalit A/S Pressalitvej 1 DK-8680 Ry Tel.: +45 8788 8788 Fax: +45 8788 8789 E-mail: pressalit@pressalit.com