



# PRESSALIT®

## Pressalit Sway D2 994

Toilet seat with soft close and lift-off incl. hinge in stainless steel

### Features

Lift-off, Soft close

### Item number

994001-DF4999  
VVS:615064001  
NRF:6190163  
RSK:7821822  
EAN:5708590341941

With its well-composed lines, SWAY D2 demonstrates how slimness and self-assurance can work together. Spoil yourself with a seat that is the perfect match for your stylish lifestyle.






### Colour

Black (RAL 9005)

### Description

PRESSALIT toilet seat with cover, model "Pressalit Sway D2", art. no. 994 made of colour ingrained duroplast with soft close incl. DF4 universal toggle hinge with lift-off in stainless steel.

- dismounting of seat/cover makes cleaning easier
- centre distance: 110-237 mm
- load - ring seat 240 kg
- 10 year guarantee



### Design type

Sandwich

### Designer

Pressalit

### Design year

2016



---

**Pressalit Sway D2 994****Toilet seat with soft close and lift-off incl. hinge in stainless steel**

---

<b>Materials</b>	<p><b>TOILET SEAT:</b> The material is colour ingrained duroplast (UF A 10 = urea formaldehyde) that contains no environmentally hazardous substances. UF plastic comprises 67% urea formaldehyde resin, 28% cellulose, as well as 5% minerals, pigments, lubricants and moisture content. The raw material from the supplier contains up to 0.03% free formaldehyde and even less following curing.</p> <p><b>BUFFERS:</b> EVA (copolymer made of ethylene and vinyl acetate).</p> <p><b>DAMPER KIT</b> (only relevant for toilet seats with soft close): Hydraulic damper with stainless steel damper casing and thermoplastic parts.</p> <p><b>MOUNT/HINGES:</b> Stainless steel model W. no. 1.4301/M and thermoplastic.</p>
<b>Product capacity</b>	Load - ring seat 240 kg
<b>Weight</b>	3,49 kg
<b>Carton size</b>	490x389x84 mm
<b>Gross weight</b>	4,099 kg
<b>Crate size</b>	502x401x428 mm
<b>Weight per crate</b>	20,495 kg
<b>Qty per crate</b>	5
<b>Crates per pallet</b>	12
<b>Qty per pallet</b>	60
<b>Cleaning</b>	Use a mild soap solution to clean the seat. Please take care that the seat and hinges are not left damp. Dry off any residual water or cleaning agent with a soft cloth. Avoid contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make sure that the seat and cover are kept in an upright position until all cleaning agent has been flushed away.



# PRESSALIT®

---

**Pressalit Sway D2 994****Toilet seat with soft close and lift-off incl. hinge in stainless steel**

---

**Warranty**

Your Pressalit toilet seat is subject to a 10-year product warranty against presentation of receipt. You should contact the dealer or store where you purchased the seat in the event of a complaint. In the event of complaints about defective materials and/or manufacturing defects and/or functional limitations ascertained within a 10-year period, following proper use and cleaning of the toilet seat (we reserve the right to examine the toilet seat at our factory), Pressalit will deliver spare parts or replace the toilet seat by an identical or similar model. If the color is no longer available, Pressalit reserves its right to replace the toilet seat by a similar model in the color white. Upon replacement or delivery of a spare part, the warranty period will not be extended nor renewed. If replacement is not possible, Pressalit may instead refund the purchase price.

Subject to changes in the product range, technical changes and printing errors.

---

[pressalit.com](http://pressalit.com)

---