

# PRESSALIT.

### Pressalit Projecta D Solid Pro 1008 Toilet seat with soft close and Polygiene®, incl. Solid Pro hinge

1008011-DG4925

NRF:6190291

EAN:5708590345451

D-shaped seat, which is well suited to the project market. With an antibacterial Polygiene effect. Harmonious design, ultimate strength and sturdy fittings with optimum stability - even during sideways transfer. Integrated soft

closing function - the first on the market.

Color White

Description

PRESSALIT toilet seat with cover, model "Projecta D Solid Pro", art.no. 1008 made of colour ingrained duroplast with polygiene incl. DG4 combi hinge,


universal.


- built-in soft close function

- centre distance: 145-210 mm

- load - ring seat 240 kg

- 10 year guarantee





Design typeSandwichDesignerPressalitDesign year2016



## PRESSALIT.

#### Pressalit Projecta D Solid Pro 1008 Toilet seat with soft close and Polygiene®, incl. Solid Pro hinge

Materials TOILET SEAT:

The material is colour ingrained duroplast (UF A 10 = urea formaldehyde) that contains no environmentally hazardous substances. UF plastic comprises 67% urea formaldehyde resin, 28% cellulose, as well as 5% minerals, pigments, lubricants and moisture content. The raw material from the supplier contains up to 0.03% free formaldehyde and even less following curing.

POLYGIENE (only relevant for toilet seats with polygiene):

Polygiene consists of biocide silver chloride, which has an anti-bacterial effect. This is why the bacteria growth is hampered 24 hours a day.

**BUFFERS**:

EVA (copolymer made of ethylene and vinyl acetate).

DAMPER KIT (only relevant for toilet seats with soft close):

Hydraulic damper with stainless steel damper casing and thermoplastic parts.

MOUNT/HINGES:

Stainless steel model W. no. 1.4301/M, thermoplastic semi-crystalline polyamides with partially aromatic content. Aluminium profile EN AW-6063-TS.

Product capacity Load - ring seat 240 kg

Weight 3,084 kg

Carton size 465x388x89 mm

Gross weight 3,424 kg

**Crate size** 517x399x456 mm

Weight per crate 17,12 kg

Qty per crate 5

Crates per pallet 8

Qty per pallet 40

Cleaning

Use a mild soap solution to clean the seat. Please take care that the seat and hinges are not left damp. Dry off any residual water or cleaning agent with a soft cloth. Avoid

contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make sure that the seat and cover are kept in an upright position until all cleaning agent has

been flushed away.



# PRESSALIT.

Pressalit Projecta D Solid Pro 1008
Toilet seat with soft close and Polygiene®, incl. Solid Pro hinge

#### Warranty

Your Pressalit toilet seat is subject to a 10-year product warranty against presentation of receipt. You should contact the dealer or store where you purchased the seat in the event of a complaint.<br/>

| Strict | Stri

Subject to changes in the product range, technical changes and printing errors.

pressalit.com

Pressalit A/S Pressalitvej 1 DK-8680 Ry Tel.: +45 8788 8788 Fax: +45 8788 8789 E-mail: pressalit@pressalit.com

PRESSALIT: