

PRESSALIT.

Product Item number	PLUS shower seat 310, fixed height R7304035	
	NRF:6317085	
	EAN:5708590359304	
	HMI: 121181	
	FDA: INN/D135865	
Colour	Red (RAL 3003)	
Product description	PLUS shower seats are offered in a number of colours. They are available as b fixed height, electrically adjustable and manually adjustable, and with an option back and armrests. They are suitable for wall-mounting or for fitting to Pressalit PLUS wall tracks.	
	PLUS shower seat 310. For fixed mounting. The seat is foldable. Materials: Comfortable polyurethane foam over a plywood core, fitted to an aluminiu profile. Excl. mounting kit. Replaces R7310	
Adjustability	Fixed mounting	
Product capacity	Maximum user mass: 200 kg. When the seat is loaded with 200 kg, each wall fastener is loaded with 113 kg. The seat has been tested statically with safety factor 1.5, which is a requirement according to the applied assistive products standards.	
Materials	The shower seat is made of polyurethane (PU) foam with a plywood core and this is covered with an in-mould coated surface that is protected using a clear PU lacquer. Internal components and fasteners are primarily made of stainless steel. The hinge barrel is capped with ABS.	
Ergonomy	Ergonomically designed seat - contact surface are 450×437 mm. Soft and slip-resistant material that has a warm feel.	
Features	The seat can fold up when not in use or to maximise floor space.	
Warranty	Pressalit makes a commitment to remedy material and manufacturing defects for a period of five years from the invoicing date.	



PRESSALIT.

Product	PLUS shower seat 310, fixed height		
Item number	R7304035		
Cleaning	PLUS shower seat. The product is to be cleaned with hot water or a mild soapy cleaning agent. Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged.		
	The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container.		
	DISINFECTANTS: Erisan OXY+ Tvättsprit 70% CaviCide surface disinfectant decontaminant cleaner Rodalon Desinfektionsspray Terralin protect (SCHÜLKE+) Dismonzon Plus (BODE Chemie GmbH)		
	NON-DISINFECTANTS: Wetrok Caledor (Wetrok) Petrosol Citro (Büfa)		
	Important: Polyurethane surfaces of PLUS shower seats and PLUS backrests contains an antibacterial surface, which will be compromised if cleaned with anything other than soap and water.		
	The product must be wiped down with a soft rag wrung out in clear water immediately after cleaning, as some materials may otherwise be discolored and stained, and the surface coating may deteriorate.		
	DECALCIFICATION OF ALUMINUM PARTS: Pressalit recommends that chalky deposits be removed from wall tracks and other aluminum parts using a solution of three parts 30% acetic acid to seven parts tap water. When the aluminum parts have been washed down with this solution, the parts must be wiped over with a damp cloth wrung out in clear water.		
Declaration of conformity	CE MDR This product is in compliance with all relevant requirements of: - Regulation (EU) 2017/745 on medical devices.		



PRESSALIT.

Produc	t
--------	---

PLUS shower seat 310, fixed height

Item number

R7304035

Installation in different wall types


a. V. O. C	
Z. 7 a. 0 a. 0	
C. C. C. C. V. Z	
2 . D . C . D . C	

Concrete >B25

V8604 - Mounting kit, 4 countersunk screws Ø8 x 70, plugs SX10.

To be ordered separately.







Solid Brick >= Mz12

V8604 - Mounting kit, 4 countersunk screws Ø8 x 70, plugs SX10.

To be ordered separately.





Solid Sand Lime Brick >= Hlz12

V8604 - Mounting kit, 4 countersunk screws \emptyset 8 x 70, plugs SX10.

To be ordered separately.







Aerated Concrete P4

V8654 - Mounting kit, 4 countersunk bolts M8 x 35, plugs FTP M 8.

To be ordered separately.






Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood

V8604 - Mounting kit, 4 countersunk screws Ø8 x 70, plugs SX10. NB! Plugs are not needed.

To be ordered separately.





PRESSALIT®

Product Item number	PLUS shower seat 310, fixed height R7304035	
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood Wall fasteners (4 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.	
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (2 mm) Wall fasteners (4 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.	
	Drywall (2 x 12,5 mm) water-resistant	
	Mounting in this wall type is not recommended - risk of fatal injury to persons and walls.	!

It is the responsibility of the installer to ensure that suitable wall fasteners are used.

pressalit.com