

PRESSALIT.

Product	PLUS shower seat 450, manually height adjustable		
Item number	R7414277		
	NRF:6317111	$\sum_{i=1}^{n}$	
	EAN:5708590359571	604	
	HMI: 124329		
	FDA: INN/D135865		
Colour	Lime green	424 450 437	
Product description	 PLUS shower seats are offered in a number of colours. They are available as bot fixed height, electrically adjustable and manually adjustable, with and without aperture, and with an option of back and armrests. They are suitable for wall-mounting or for fitting to Pressalit PLUS wall tracks. PLUS shower seat 450. Manually height adjustable by 240 mm, without the use of tools. The seat is foldable. Materials: Comfortable polyurethane foam over a plywood core, fitted to an alumin profile. Excl. mounting kit. <i>Replaces R7410</i> 		
Adjustability	Height adjustable		
Adjustment height	240 mm		
Product capacity	Maximum user mass: 200 kg. When the seat is loaded with 200	imum user mass: 200 kg. In the seat is loaded with 200 kg, each wall fastener is loaded with 47 kg.	
	The seat has been tested statically with safety factor 1.5, which is a requirement according to the applied assistive products standards.		
Materials	The shower seat is made of polyurethane (PU) foam with a plywood core and this is covered with an in-mould coated surface that is protected using a clear PU lacquer Internal components and fasteners are primarily made of stainless steel. The hinge barrel is capped with ABS.		
Ergonomy		Ergonomically designed seat - contact surface are 450 x 437 mm. Soft and slip- esistant material that has a warm feel.	
Features	The seat can fold up when not in use or to maximise floor space.		





Product	PLUS shower seat 450, manually height adjustable		
ltem number	R7414277		
Warranty	Pressalit makes a commitment to remedy material and manufacturing defects for period of five years from the invoicing date.		
Cleaning	PLUS shower seat. The product is to be cleaned with hot water or a mild soapy cleaning agent. Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged.		
	The following cleaning agents have been tested by Pressalit and may be used, a long as they are diluted according to the instructions on the container.		
	DISINFECTANTS: Erisan OXY+ Tvättsprit 70% CaviCide surface disinfectant decontaminant cleaner Rodalon Desinfektionsspray Terralin protect (SCHÜLKE+) Dismonzon Plus (BODE Chemie GmbH)		
	NON-DISINFECTANTS: Wetrok Caledor (Wetrok) Petrosol Citro (Büfa)		
	Important: Polyurethane surfaces of PLUS shower seats and PLUS backrests contains an antibacterial surface, which will be compromised if cleaned with anyth other than soap and water.		
	The product must be wiped down with a soft rag wrung out in clear water immedi after cleaning, as some materials may otherwise be discolored and stained, and surface coating may deteriorate.		
	DECALCIFICATION OF ALUMINUM PARTS: Pressalit recommends that chalky deposits be removed from wall tracks and other aluminum parts using a solution of three parts 30% acetic acid to seven parts tap water. When the aluminum parts have been washed down with this solution, the must be wiped over with a damp cloth wrung out in clear water.		
Declaration of conformity	CE MDR This product is in compliance with all relevant requirements of: - Regula (EU) 2017/745 on medical devices.		



PRESSALIT.

Product

Item number

PLUS shower seat 450, manually height adjustable R7414277

Installation in different wall types

α. V · Q · Q · Q · Q · Q · Q · Q · Q · Q ·	Concrete >B25 V8610 - Mounting kit, 8 coach screws Ø8 x 70, plugs SX10. To be ordered separately.	
	Solid Brick >= Mz12 V8610 - Mounting kit, 8 coach screws Ø8 x 70, plugs SX10. To be ordered separately.	
	Solid Sand Lime Brick >= HIz12 V8610 - Mounting kit, 8 coach screws Ø8 x 70, plugs SX10. To be ordered separately.	
	Aerated Concrete P4 V8660 - Mounting kit, 8 countersunk bolts M8 x 35, plugs FTP M 8. To be ordered separately.	
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood V8610 - Mounting kit, 8 coach screws Ø8 x 70, plugs SX10. NB! Plugs are not needed. To be ordered separately.	



PRESSALIT.

Product Item number	PLUS shower seat 450, manually height adjustable R7414277	
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood Wall fasteners (8 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.	
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (2 mm) Wall fasteners (8 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.	
	Drywall (2 x 12,5 mm) water-resistant Wall fasteners (8 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.	

pressalit.com

Pressalit A/S Pressalitvej 1 DK-8680 Ry Tel.: +45 8788 8788 Fax: +45 8788 8789 E-mail: pressalit@pressalit.com