

## PRESSALIT.

Product Item number	PLUS backrest, fixed height R6404000
Color	VVS:777530200 NRF:6317031 EAN:5708590365350 HMI: 124215 White
Product description	PLUS backrests are offered in a number of colours and versions, they are available as both fixed height and adjustable.  They are suitable for wall-mounting behind a toilet without cistern or mounting on one of Pressalit's toilet lifters.  PLUS backrest, 15.2" x 8.2", soft feel.  Fixed height, for mounting directly on the wall behind a wall-mounted elongated toilet without cistern.  Materials: Aluminium and polyurethane foam with a plywood core.  Incl. mounting bolts for brick wall. Plugs depend on wall type and must be ordered separately.
Adjustability Product capacity	Fixed mounting  Maximum load: 110 lbs.  Maximum user weight: 220 lbs.  When the backrest is loaded with 110 lbs, each wall fastener will be carrying 260 lbs.  Backrests need to be able to support the weight of the person who is leaning against it.  The backrest is not intended to carry the full body weight of a person, and the test methods applicable to backrests reflect this: ISO 17966 prescribes a static test at 50% of maximum user weight, i.e. when the maximum load on a wash basin bracket is given as 110 lbs, it is – according to ISO 17966 – the equivalent of a user weighing 220 lbs leaning on the backrest.
Materials	The backrest is made of polyurethane (PU) foam which is covered with a moulded coated surface that is protected using a clear PU lacquer.
Ergonomy	Soft and slip-resistant material that has a warm feel.
Warranty	Pressalit makes a commitment to remedy material and manufacturing defects for a period of five years from the invoicing date.



## PRESSALIT.

Product	PLUS backrest, fixed height
Item number	R6404000
Cleaning	This product should be cleaned with hot water or a mild cleaning solution.  Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged.
	The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container.
	DISINFECTANTS: Erisan OXY+ Tvättsprit 70% CaviCide surface disinfectant decontaminant cleaner Rodalon Desinfektionsspray Terralin protect (SCHÜLKE+) Dismonzon Plus (BODE Chemie GmbH)
	NON-DISINFECTANTS: Wetrok Caledor (Wetrok) Petrosol Citro (Büfa)
	Important: Polyurethane surfaces of PLUS shower seats and PLUS backrests contains an antibacterial surface, which will be compromised if cleaned with anything other than soap and water.
	The product must be wiped down with a soft rag wrung out in clear water immediately after cleaning, as some materials may otherwise be discolored and stained, and the surface coating may deteriorate.
Declaration of conformity	DECALCIFICATION OF ALUMINUM PARTS: Pressalit recommends that water deposits (Calcium, lime etc.) be removed from wall tracks and other aluminum parts using a solution of three parts of 30% acetic acid to seven parts tap water. When the aluminum parts have been washed down with this solution, the parts should be wiped over with a damp cloth wrung out in plain water.  This product is in compliance with all relevant requirements of regulation (EU) 2017/745 on medical devices.



## PRESSALIT®

Product PLUS backrest, fixed height

Item number R6404000

pressalit.com

Pressalit A/S
Pressalitvej 1
DK-8680 Ry
Tel.: +45 8788 8788
Fax: +45 8788 8789
E-mail: pressalit@pressalit.com