

# PRESSALIT®

#### Pressalit Sway D 934 Toilet seat with soft close and lift-off incl. hinge in stainless steel

Features Lift-off, Soft close

1tem number 934230-BL6999

VVS:615055230 NRF:6190307 RSK:7821898

EAN:5708590365619

With its well-composed lines, SWAY D demonstrates how slimness and self-assurance can work together. Spoil yourself with a seat that is the perfect match for

your stylish lifestyle.

Colour Matt white

**Description**PRESSALIT toilet seat with cover, model "Pressalit Sway D", art. no. 934 made of colour ingrained


duroplast with BL6 universal toggle hinge with lift-off of


stainless steel.


- centre distance: 141-219 mm

- load - ring seat 240 kg

- 10 year guarantee







**Design type** Sandwich

**Designer** Pressalit

Design year 2015



## PRESSALIT.

Pressalit Sway D 934
Toilet seat with soft close and lift-off incl. hinge in stainless steel

Materials TOILET SEAT:

The material is colour ingrained duroplast (UF A 10 = urea formaldehyde) that contains no environmentally hazardous substances. UF plastic comprises 67% urea formaldehyde resin, 28% cellulose, as well as 5% minerals, pigments, lubricants and moisture content. The raw material from the supplier contains up to 0.03% free formaldehyde and even less following curing.

....

EVA (copolymer made of ethylene and vinyl acetate).

DAMPER KIT (only relevant for toilet seats with soft close):

Hydraulic damper with stainless steel damper casing and thermoplastic parts.

MOUNT/HINGES:

Stainless steel model W. no. 1.4301/M and thermoplastic.

Product capacity Load - ring seat 240 kg

Weight 3,016 kg

Carton size 488x388x72 mm

Gross weight 3,625 kg

**Crate size** 500x400x368 mm

Weight per crate 18,125 kg

Qty per crate 5

Crates per pallet 18

Qty per pallet 90

Cleaning

Use a mild soap solution to clean the seat. Please take care that the seat and hinges are not left damp. Dry off any residual water or cleaning agent with a soft cloth. Avoid contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as

these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make sure that the seat and cover are kept in an upright position until all cleaning agent has

been flushed away.



## PRESSALIT.

Pressalit Sway D 934
Toilet seat with soft close and lift-off incl. hinge in stainless steel

#### Warranty

Your Pressalit toilet seat is subject to a 10-year product warranty against presentation of receipt. You should contact the dealer or store where you purchased the seat in the event of a complaint. In the event of complaints about defective materials and/or manufacturing defects and/or functional limitations ascertained within a 10-year period, following proper use and cleaning of the toilet seat (we reserve the right to examine the toilet seat at our factory), Pressalit will deliver spare parts or replace the toilet seat by an identical or similar model. If the color is no longer available, Pressalit reserves its right to replace the toilet seat by a similar model in the color white. Upon replacement or delivery of a spare part, the warranty period will not be extended nor renewed. If replacement is not possible, Pressalit may instead refund the purchase price.

Subject to changes in the product range, technical changes and printing errors.

pressalit.com

Pressalit A/S Pressalitvej 1 DK-8680 Ry Tel.: +45 8788 8788 Fax: +45 8788 8789 E-mail: pressalit@pressalit.com

PRESSALIT: