

PRESSALIT®

Pressalit Privilege 532 Standard toilet seat incl. hinge in stainless steel

532000-UN3999 Item number

EAN:5708590299242

Pressalit Privilege is a reinforced seat, particularly suited for the project market as it is furnished with stabilizing

buffers that lock the seat to the pan.


Colour White


Description PRESSALIT toilet seat with cover, model "Privilege", art. no. 532 made of colour ingrained duroplast with UN3 stainless steel hinge.


- centre distance: 155 mm

- load - ring seat 240 kg suitable for many universal toilets

- 10 year guarantee







Sandwich **Design type**

Designer Pressalit

Design year 2006



PRESSALIT.

Pressalit Privilege 532 Standard toilet seat incl. hinge in stainless steel

Materials TOILET SEAT:

The material is colour ingrained duroplast (UF A 10 = urea formaldehyde) that contains no environmentally hazardous substances. UF plastic comprises 67% urea formaldehyde resin, 28% cellulose, as well as 5% minerals, pigments, lubricants and moisture content. The raw material from the supplier contains up to 0.03% free formaldehyde and even less following curing.

POLYGIENE (only relevant for toilet seats with polygiene):

Polygiene consists of biocide silver chloride, which has an anti-bacterial effect. This is why the bacteria growth is hampered 24 hours a day.

BUFFERS:

EVA (copolymer made of ethylene and vinyl acetate).

DAMPER KIT (only relevant for toilet seats with soft close):

Hydraulic damper with stainless steel damper casing and thermoplastic parts.

MOUNT/HINGES:

Stainless steel model W. no. 1.4301/M and thermoplastic.

Product capacity Load - ring seat 240 kg

Weight 3,0569 kg

Carton size 490x389x84 mm

Gross weight 3,4569 kg

Crate size 502x401x428 mm

Weight per crate 17,2845 kg

Qty per crate 5

Crates per pallet 12

Qty per pallet 60

Cleaning Use a mild soap solution to clean the seat. Please take care that the seat and hinges are

not left damp. Dry off any residual water or cleaning agent with a soft cloth. Avoid contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make sure that the seat and cover are kept in an upright position until all cleaning agent has

been flushed away.



PRESSALIT.

Pressalit Privilege 532 Standard toilet seat incl. hinge in stainless steel

Warranty

Your Pressalit toilet seat is subject to a 10-year product warranty against presentation of receipt. You should contact the dealer or store where you purchased the seat in the event of a complaint.

| Strict | Stri

Subject to changes in the product range, technical changes and printing errors.

pressalit.com

Pressalit A/S Pressalitvej 1 DK-8680 Ry Tel.: +45 8788 8788 Fax: +45 8788 8789 E-mail: pressalit@pressalit.com

PRESSALIT: