




|  |   |
|--|---|
| <p><b>Product</b></p> <p><b>Item number</b></p>  | <p>PLUS support arm with integrated counter-balance, 850 mm, left hand operated</p> <p>R391385108</p>   |
| <p><b>Colour</b></p> <p><b>Product description</b></p>                                     | <p>NRF:6191163<br/> EAN:5708590368900<br/> HMI: 125890<br/> FDA: ILS/D135866</p> <p>Dark blue (RAL 5011)</p>  <p>All PLUS support arms come with an integrated counter-balance, which ensures a controlled movement between horizontal and vertical positions. Suitable for use with toilet pans projecting 700 mm or floor standing toilets. <i>Replaces discontinued models R3575 og RF575.</i></p> <p>PLUS support arm, counter-balanced. Projection 920 mm, ergonomically shaped to provide a clear sense of where the support arm ends. Left hand operated. Height adjustable by 240 mm and sideways adjustable. Detachable and foldable. Anthracite cover plate for vertical wall track.</p> <p>Materials: The arms are constructed of 10-micrometre anodized aluminium, with a non-slip gripping surface made of soft SEBS incorporating a glass-reinforced nylon core<br/> For fitting to horizontal PLUS wall track (not included).</p> |
| <p><b>Adjustability</b></p> <p><b>Adjustment height</b></p> <p><b>Product capacity</b></p> | <p>Height and sideways adjustable</p> <p>240 mm</p> <p>Maximum load: 150 kg.<br/> When the support arm is loaded with 150 kg, each wall fastener in the horizontal wall track is loaded with 44 kg.</p> <p><i>PLUS support arms have been tested statically with 700 kg (close to the wall), 425 kg (in the middle) and 225 kg (the outermost point).</i></p>   |
| <p><b>Materials</b></p>  | <p>The arms are primarily constructed in 10-micrometre anodized aluminium, with a non-slip gripping surface at the end made of soft SEBS and incorporating a glass-reinforced nylon core.</p> <p>The hinge arm is also made of soft SEBS.</p> <p>Internal components and fasteners are primarily made of stainless steel.</p> <p>The hinge barrel is capped with ABS polymer.</p>   |



# PRESSALIT®

|                    |   |
|--------------------|---|
| <b>Product</b>     | PLUS support arm with integrated counter-balance, 850 mm, left hand operated  |
| <b>Item number</b> | R391385108  |
| <b>Ergonomy</b>    | <p>The oval shape gives an easy and comfortable surface to lean and push against.</p> <p>The end of the support arm is enlarged so that it is easier to pull forward from a sitting position and also provides a clear sense of where the support arm ends.</p> <p>Soft and slip-resistant material that has a warm feel.</p> |
| <b>Features</b>    | <p>Folds against the wall.</p> <p>The underside is shaped for the mounting of various accessories.</p>  |
| <b>Warranty</b>    | Pressalit makes a commitment to remedy material and manufacturing defects for a period of five years from the invoicing date.   |



|                                  |  |
|----------------------------------|--|
| <b>Product</b>                   | PLUS support arm with integrated counter-balance, 850 mm, left hand operated   |
| <b>Item number</b>               | R391385108   |
| <b>Cleaning</b>                  | <p>PLUS support arms.<br/>The product is to be cleaned with hot water or a mild soapy cleaning agent.<br/>Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged.</p> <p>The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container.</p> <p><b>DISINFECTANTS:</b><br/>Clinimax Difficil-S<br/>Erisan OXY+<br/>Sprit (husholdningssprit)<br/>Suma Bac D10<br/>Virkon<br/>Rodalon Desinfektionsspray<br/>Lysoformin Spezial<br/>CaviCide<br/>Sufanios Premium<br/>Tvättsprit 70%<br/>Oxyplus-acid 2% (Diversey)<br/>WipeClean UniversalCleaning<br/>Chlorine Disinfection Wipes</p> <p><b>NON-DISINFECTANTS:</b><br/>Suma Star free D1<br/>Taski 100<br/>Taski 200<br/>Milizid Citro</p> <p>The product must be wiped down with a soft rag wrung out in clear water immediately after cleaning, as some materials may otherwise be discolored and stained, and the surface coating may deteriorate.</p> <p><b>DECALCIFICATION OF ALUMINUM PARTS:</b><br/>Pressalit recommends that chalky deposits be removed from wall tracks and other aluminum parts using a solution of three parts 30% acetic acid to seven parts tap water. When the aluminum parts have been washed down with this solution, the parts must be wiped over with a damp cloth wrung out in clear water.</p> |
| <b>Declaration of conformity</b> | CE MDR This product is in compliance with all relevant requirements of: - Regulation (EU) 2017/745 on medical devices.   |



# PRESSALIT®

|                    |  |
|--------------------|--|
| <b>Product</b>     | PLUS support arm with integrated counter-balance, 850 mm, left hand operated   |
| <b>Item number</b> | R391385108   |
|                    | <p><b>Intended use</b><br/>The support arm is used as a support for sitting down or getting up from a toilet, or for sideways transfer from a wheelchair.</p> <p><b>Operating environment</b><br/>For indoor use in a wet environment, such as a bathroom or a washroom, in private homes, nursing homes and hospitals.<br/>For institutional use, the expected life time is 10 years.<br/><i>Life cycle test performed according to ISO 17966:2016.</i></p> <p>For maintenance, please refer to user guide, which is enclosed with the product, and which can also be found on the website under "Downloads".</p> |

---

[pressalit.com](http://pressalit.com)

---

Pressalit A/S  
Pressalitvej 1  
DK-8680 Ry  
Tel.: +45 8788 8788  
Fax: +45 8788 8789  
E-mail: [pressalit@pressalit.com](mailto:pressalit@pressalit.com)

PRESSALIT®