

Product	PLUS wall track, 400 mm, left-grooved, for vertical mounting		
Item number	R9873112		
	VVS:615843134		
	NRF:7501072		
	EAN:5708590369280		
	HMI: 124111		
Colour	Anthracite grey		
Product description	Below a selection of products for fitting to the wall track.		
	PLUS wall track, 400 mm, left-grooved, for vertical mounting. For height adjustable, left-hand operated support arms. The cover plate hides bolts and wires and facilitates cleaning. Materials: Aluminium and polystyrene. Excl. mounting kit.		
Adjustability	Fixed mounting		
Materials	The wall track is primarily made of 10-micrometre anodized aluminium. The cover plate is made of polystyrene and the ends of the track are capped with ABS polyme		
Ergonomy	The vertical track enables height adjustment of the different products. If combined with the horizontal track, the available space in the bathroom can be utilized optimally. In environments with multiple users, the vertical track makes it possible to adjust the different products to individual user heights.		
Features	The front cover plate conceals mounting bolts and any cables.		
Warranty	Pressalit makes a commitment to remedy material and manufacturing defects for a period of five years from the invoicing date.		



Product PLUS wall track, 400 mm, left-grooved, for vertical mounting			
ltem number	R9873112		
Cleaning			
	PLUS wall tracks.		
	The product is to be cleaned with hot water or a mild soapy cleaning agent.		
	Do not use chlorine based, corrosive or abrasive cleaners as it may result in the		
	surface being damaged.		
	The following cleaning agents have been tested by Pressalit and may be used, a		
	long as they are diluted according to the instructions on the container.		
	DISINFECTANTS:		
	Clinimax Difficil-S		
	Erisan OXY+		
	Sprit (husholdningssprit)		
	Suma Bac D10		
	Virkon		
	Rodalon Desinfektionsspray		
	Lysoformin Spezial		
	CaviCide		
	Sufanios Premium		
	Tvättsprit 70%		
	NON-DISINFECTANTS:		
	Suma Star free D1		
	Taski 100		
	Taski 200		
	Milizid Citro		
	The product must be wiped down with a soft rag wrung out in clear water immedi		
	after cleaning, as some materials may otherwise be discolored and stained, and		
	surface coating may deteriorate.		
	DECALCIFICATION OF ALUMINUM PARTS:		
	Pressalit recommends that chalky deposits be removed from wall tracks and other		
	aluminum parts using a solution of three parts 30% acetic acid to seven parts tap		
	water. When the aluminum parts have been washed down with this solution, the		
	must be wiped over with a damp cloth wrung out in clear water.		
Declaration of	MDR-ACC This product fulfils all relevant requirements in Regulation (EU) 2017/		
conformity	on medical devices in risk class I. This product is considered to be an accessory		
	a medical device, as it is not itself a medical device, but is intended to be used		
	together with several particular medical devices to specifically enable the medica		



Product

Item number

PLUS wall track, 400 mm, left-grooved, for vertical mounting R9873112

Installation in different wall types

Concrete >B25 V8610 - Mounting kit, 8 coach screws Ø8 x 70, plugs SX10. To be ordered separately.	
Solid Brick >= Mz12 V8610 - Mounting kit, 8 coach screws Ø8 x 70, plugs SX10. To be ordered separately.	
Solid Sand Lime Brick >= HIz12 V8610 - Mounting kit, 8 coach screws Ø8 x 70, plugs SX10. To be ordered separately.	
Aerated Concrete P4 V8660 - Mounting kit, 8 countersunk bolts M8 x 35, plugs FTP M 8. To be ordered separately.	
Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood V8610 - Mounting kit, 8 coach screws Ø8 x 70, plugs SX10. NB! Plugs are not needed. To be ordered separately.	



Product Item number	PLUS wall track, 400 mm, left-grooved, for vertical m R9873112	ounting
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood Wall fasteners (8 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.	
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (2 mm) Wall fasteners (8 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.	
	Drywall (2 x 12,5 mm) water-resistant Mounting in this wall type is not recommended - risk of fatal injury to persons and walls.	

It is the responsibility of the installer to ensure that suitable wall fasteners are used.

pressalit.com

Pressalit A/S Pressalitvej 1 DK-8680 Ry Tel.: +45 8788 8788 Fax: +45 8788 8789 E-mail: pressalit@pressalit.com

