

Product	PLUS handrail corner shower combination, reversible left/right, 762 x 762 x 1250 mm		
Item number	RT156112		
	VVS:777568682		
	NRF:6317194		
	EAN:5708590371146		
	HMI: 125873		
Colour	Anthracite grey		
Product description	PLUS handrails are high-quality products and they can be combined in countless ways and they provide the final touch to furnishing a functional and flexible bathroor A reliable solution with many different options, which can easily lay the grounds for increased independence.		
	PLUS handrail combination, 33 mm, reversible right/left, A: 762 mm x B: 762 mm x 1250 mm, for fixed mounting. The projection of 50 mm from the wall makes it easy to take hold of the rail. Inkl. wall rosette, which covers the fixings. Material: Powder-coated aluminium and plastic. Excl. mounting kit.		
Product capacity	Maximum load: 235 kg. When the handrail is loaded with 235 kg, each wall fastener is loaded with 56 kg. Handrails are tested with a 1.5 safety factor in accordance with the requirements in ISO 17966:2016.		
Materials	Basic material: Aluminium		
	Surface material: Polyester lacquer		
	Cover cap: Cycoloy plastic		
	Strap: Nylon (PA)		
Ergonomy	The 33 mm diameter enables the rail to be held comfortably and firmly. The projection of 50 mm from the wall makes it easy to take hold of the rail.		
	Pressalit makes a commitment to remedy material and manufacturing defects for a period of five years from the invoicing date.		



Product	PLUS handrail corner shower combination, reversible left/right, 762 x 762 1250 mm		
Item number	RT156112		
Cleaning			
	Handrails ALU. The product is to be cleaned with hot water or a mild soapy cleaning agent. Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged.		
	The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container.		
	DISINFECTANTS: Clinimax Difficil-S Erisan OXY+		
	NON-DISINFECTANTS: Suma Star free D1 Taski 100 Taski 200		
	The product must be wiped down with a soft rag wrung out in clear water immediat after cleaning, as some materials may otherwise be discolored and stained, and th surface coating may deteriorate.		
	DECALCIFICATION OF ALUMINUM PARTS: Pressalit recommends that chalky deposits be removed from wall tracks and other aluminum parts using a solution of three parts 30% acetic acid to seven parts tap water. When the aluminum parts have been washed down with this solution, the pa must be wiped over with a damp cloth wrung out in clear water.		
Declaration of conformity	CE UK MDR This product is in compliance with all relevant requirements of: - Regulation (EU) 2017/745 on medical devices. For the UK: - Medical Device Regulation (MDR) 2002 on medical devices.		



Product 1250 mm	er shower combination, reversible left/right, 762 x 762 x
Item number RT156112	

Installation in different wall types

a. V. Q. a. V. G. a. V. Q. a. V. G. a. V. A. B. Q. A. V. A. D. A. C. V. A. C. Q. Q. A. C. A. C. Q. Q. a. V. Q. A. C. Q. a. V. Q. A. C. Q. Q. a. V. A. B. A. C.	Concrete >B25 V8618 - Mounting kit, 16 screws Ø5 x 50 - plugs SX8, for brick wall. Must be ordered separately.	
	Solid Brick >= Mz12 V8618 - Mounting kit, 16 screws Ø5 x 50 - plugs SX8, for brick wall. Must be ordered separately.	
	Solid Sand Lime Brick >= HIz12 V8618 - Mounting kit, 16 screws Ø5 x 50 - plugs SX8, for brick wall. Must be ordered separately.	
	Aerated Concrete P4 V8668 - Mounting kit, 16 bolts M5 x 50 - plugs FTP K 6. To be ordered separately.	
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood V8618 - Mounting kit, 16 screws Ø5 x 50 - plugs SX8. NB! Plugs are not needed. To be ordered separately.	



PLUS handrail corner shower combination, reversible left/right, 762 x 7 1250 mm		
RT156112		
Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood Wall fasteners (16 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.		
Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (2 mm) Wall fasteners (16 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.		
Drywall (2 x 12,5 mm) water-resistant		
Mounting in this wall type is not recommended - risk of fatal injury to persons and walls.		
	1250 mmRT156112Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywoodWall fasteners (16 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (2 mm)Wall fasteners (16 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (2 mm)Wall fasteners (16 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.Drywall (2 x 12,5 mm) water-resistant Mounting in this wall type is not recommended - risk of	

pressalit.com

Pressalit A/S Pressalitvej 1 DK-8680 Ry Tel.: +45 8788 8788 Fax: +45 8788 8789 E-mail: pressalit@pressalit.com

