

PRESSALIT.

Product Item number	SCT 3000 shower change table, electrically height adjustable R8592313299		
	EAN: 5708590374130 FDA: INQ/D124319		
Color	Sapphire blue (RAL 5003)		
Product description	Pressalit offers a variety of mobile and wall-hung, height-adjustable and fixed height shower and changing tables of high quality. They are designed to provide a stable platform for showering and changing adults and children with reduced mobility. These tables can be used in schools, institutions, hospitals and private homes and are all designed to be durable, comfortable and easy to clean. The design and flexibility of the tables ensures optimal working conditions for the carer as well as a high level of comfort and safety for the user.		
	The SCT 3000 series has a stylish and award-winning design focused on comfort an ease of use.		
	SCT 3000 shower change table, powered, height adjustable 27.6"; from 11.8" - 39.4", with wired hand control Foldable. Incl. safety rail, flexible hose (Ø1.26") and water collection tray with integrated outlet. Surface length 51.2", outer measurements 41.6" x 55.5". Materials: Powder-lacquered stainless steel, aluminium, polyurethane foam and polystyrene. Excl. mounting kit.		
Adjustability	Height adjustable		
Adjustment height	27,58 inch		
Product capacity	Maximum user weight (MUM): 500 lbs. Maximum load (SWL): 522 lbs. (User weight + weight of water) When the table is loaded with 500 lbs, each mounting bolt supports 65 lbs. This product has been tested statically with a load of 1306 lbs, as the IEC 60601-1 standard requires testing with a safety factor 2.5.		



PRESSALIT.®

Product	SCT 3000 shower change table, electrically height adjustable		
Item number	R8592313299		
Speed up	Speed up: 0,59 inch/s Speed down: 0,79 inch/s		
Noise level	48 dB		
Materials	Aluminium, polyurethane foam, plastics, powder-coated steel.		
Ergonomy	 The ergonomically designed safety rails have a practical lower central section, which provides better access and work environment for the carer while transferring, showering, drying, changing and dressing the user. 		
	• One hand operated safety rails allows the carer to maintain eye contact as well as physical contact with the user during the whole process.		
	• Easy to clean, smooth contact surfaces which do not collect dirt and bacteria.		
Features	•A water collection tray with integrated water outlet prevents water from splashing caregiver or the floor. The flexible hose (Ø1.26") attached to the center mounted outlet of the water collection tray, can be connected to either an outlet in the floor o on the wall.		
	The slightly curved shape makes the table comfortable and safe to lie on.		
	 Adjustable neck support which can be moved to either end of the 51.2" changing tables. 		
	•The integrated pneumatic cylinders enable the table to be folded out of the way when not in use to maximize floor space.		
	• The powered shower change table is supplied with a wired hand control. The red buttons clearly indicate "up" and "down".		
	The wired hand control comes with a practical holder for placement on the wall.		
Mains connection (V)	120		
Actuator (motor)	LA40CS Careline (Linak) 4000 N, IPX6		
Control box	SMPS14 Careline (Linak), IPX6		
Wired remote control	HB3 (Linak), IPX6		
Power consumption (maximum load)	Power consumption by maximum load: 390 W Power consumption by standby: 2 W		



PRESSALIT.®

Product	SCT 3000 shower change table, electrically height adjustable		
Item number	R8592313299		
Warranty	Pressalit makes a commitment to remedy material and manufacturing defects for a period of three years from the invoicing date. NOTICE If the product is placed in an atmosphere heavy in salt or chloride, the warranty will be reduced from the normal years to 1 year. Salt and chloride have a corrosive effect on the products componer and will cause a decrease in the life expectancy of the product.		
Cleaning			
Ğ	This product should be cleaned with hot water or a mild cleaning solution. Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged.		
	The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container.		
	DISINFECTANTS: Clinimax Difficil-S Erisan OXY+		
	Sprit (husholdningssprit) Suma Bac D10 Virkon		
	Rodalon Desinfektionsspray Lysoformin Spezial CaviCide		
	Sufanios Premium		
	Tvättsprit 70% Accel PREVention Wipes Lingettes		
	NON-DISINFECTANTS: Suma Star free D1		
	Taski 100 Taski 200		
	Milizid Citro		
	The product must be wiped down with a soft rag wrung out in clear water immedia after cleaning, as some materials may otherwise be discolored and stained, and the surface coating may deteriorate.		
	DECALCIFICATION OF ALUMINUM PARTS: Pressalit recommends that water deposits (Calcium, lime etc.) be removed from wateracks and other aluminum parts using a solution of three parts of 30% acetic acid seven parts tap water. When the aluminum parts have been washed down with this solution, the parts should be wiped over with a damp cloth wrung out in plain water.		
Declaration of conformity	This product is solely intended for the US and Canada, and has no EU declaration conformity.		



PRESSALIT®

Product			
Item	number		

SCT 3000 shower change table, electrically height adjustable

R8592313299

Mounting in different wall types

moronic wan types	
Concrete >B25 V8608 - Mounting kit, 6 lag bolts Ø10 x 70 - plugs SX12. To be ordered separately.	
Solid Brick >= Mz12 V8608 - Mounting kit, 6 lag bolts Ø10 x 70 - plugs SX12. To be ordered separately.	
Solid Sand Lime Brick >= Hlz12 V8608 - Mounting kit, 6 lag bolts Ø10 x 70 - plugs SX12. To be ordered separately.	
Aerated Concrete P4 V8658 - Mounting kit, 6 lag bolts Ø10 x 70 - plugs GB14. To be ordered separately.	
Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood V8608 - Mounting kit, 6 lag bolts Ø10 x 70 - plugs SX12. NB! Plugs are not needed. To be ordered separately.	



PRESSALIT®

Product Item number	SCT 3000 shower change table, electrically height a	djustable
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood Wall fasteners (6 pcs) must be bought separately, for drywall it is possible to use e.g. SnapTight or WingIt anchors or similar.	
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (.08 inch) Wall fasteners (6 pcs) must be bought separately, for drywall it is possible to use e.g. SnapTight or WingIt anchors or similar.	
	Drywall (2 x 12,5 mm) water-resistant	
	Mounting in this wall type is not recommended - risk of fatal injury to persons and walls.	!

It is the responsibility of the installer to ensure that suitable wall fasteners are used.

pressalit.com

Pressalit A/S
Pressalitvej 1
DK-8680 Ry
Tel.: +45 8788 8788
Fax: +45 8788 8789
E-mail: pressalit@pressalit.com

PRESSALIT.