



# PRESSALIT®

## Pressalit Chilli 1076

Toilet seat with soft close and lift-off, incl. universal hinge in stainless steel

### Item number

1076000-DL2999  
VVS:614992000  
NRF:6190766  
EAN:5708590376011

Pressalit Chilli is a stable, easy-to-clean, and safe choice for your toilet. With built-in soft close, the toilet seat lands gently and silently on the toilet, which adds a little extra luxury to your life. The soft lines and built-in lift-off function makes it easy to clean around the toilet seat, ensuring that bacteria and dirt won't be able to hide.





### Color

White

### Description

PRESSALIT toilet seat with cover, model "Pressalit Chilli", art. no. 1076 made of colour ingrained duroplast with built-in soft close function, incl. DL2 universal hinge with lift-off in stainless steel.

- dismounting of seat/cover makes cleaning easier
- centre distance: 90-170 mm
- load - ring seat 240 kg
- 10 year guarantee



### Design type

Sandwich

### Designer

Pressalit

### Design year

2020



## Pressalit Chilli 1076

Toilet seat with soft close and lift-off, incl. universal hinge in stainless steel

### Materials

#### TOILET SEAT:

The material is colour ingrained duroplast (UF A 10 = urea formaldehyde) that contains no environmentally hazardous substances. UF plastic comprises 67% urea formaldehyde resin, 28% cellulose, as well as 5% minerals, pigments, lubricants and moisture content. The raw material from the supplier contains up to 0.03% free formaldehyde and even less following curing.

#### POLYGIENE (only relevant for toilet seats with polygiene):

Polygiene consists of biocide silver chloride, which has an anti-bacterial effect. This is why the bacteria growth is hampered 24 hours a day.

#### BUFFERS:

EVA (copolymer made of ethylene and vinyl acetate).

#### DAMPER KIT (only relevant for toilet seats with soft close):

Hydraulic damper with stainless steel damper casing and thermoplastic parts.

#### MOUNT/HINGES:

Stainless steel model W. no. 1.4301/M and thermoplastic.

### Product capacity

Load - ring seat 240 kg

### Weight

2,11 kg

### Carton size

488x388x72 mm

### Gross weight

2,43 kg

### Crate size

500x400x368 mm

### Weight per crate

12,15 kg

### Qty per crate

5

### Crates per pallet

18

### Qty per pallet

90

### Cleaning

Use a mild soap solution to clean the seat. Please take care that the seat and hinges are not left damp. Dry off any residual water or cleaning agent with a soft cloth. Avoid contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make sure that the seat and cover are kept in an upright position until all cleaning agent has been flushed away.



# PRESSALIT®

---

**Pressalit Chilli 1076****Toilet seat with soft close and lift-off, incl. universal hinge in stainless steel**

---

**Warranty**

Your Pressalit toilet seat is subject to a 10-year product warranty against presentation of receipt. You should contact the dealer or store where you purchased the seat in the event of a complaint. <br><br>In the event of complaints about defective materials and/or manufacturing defects and/or functional limitations ascertained within a 10-year period, following proper use and cleaning of the toilet seat (we reserve the right to examine the toilet seat at our factory), Pressalit will deliver spare parts or replace the toilet seat by an identical or similar model. If the color is no longer available, Pressalit reserves its right to replace the toilet seat by a similar model in the color white. Upon replacement or delivery of a spare part, the warranty period will not be extended nor renewed. If replacement is not possible, Pressalit may instead refund the purchase price.

Subject to changes in the product range, technical changes and printing errors.

---

[pressalit.com](http://pressalit.com)

---

PRESSALIT®