

# PRESSALIT.

Product	SCT 2000 shower change table, coated mesh cover, electrically height adjustable	
Item number	R8571218000	
	EAN:5708590376080	
	HMI: 88223	
	NBS:N13:40,375	
Colour	White 1800	
Product description	Pressalit offers a variety of mobile and wall-hung, height-adjustable and fixed heigh shower and changing tables of high quality. They are designed to provide a stable platform for showering and changing adults and children with reduced mobility. These tables can be used in schools, institutions, hospitals and private homes and are all designed to be durable, comfortable and easy to clean. The design and flexibility of the tables ensures optimal working conditions for the carer as well as a high level of comfort and safety for the user.	
	SCT 2000 shower change table, powered, height adjustable 700 mm; from 300 mm 1000 mm, with wired hand control Foldable. Incl. safety rail and water collection tray with integrated outlet. Outer measurements 910 mm x 1800 mm. Excl. mounting kit.	
Adjustability	Height adjustable	
Adjustment height	700 mm	
Product capacity	Maximum user weight (MUM): 200 kg. Safe working load (SWL): 200 kg. When the table is loaded with 200 kg, each mounting bolt supports 26 kg This product has been tested statically with a load of 500 kg as the IEC 60601-1 standard requires testing with safety factor 2.5.	
Speed upwards	Speed up mm: 19 mm/s Speed down mm: 21 mm/s	
Noise level	50 dB	
Materials	Construction in powder-laquered stainless steel, mesh cover in PVC-coated polyeste (for extra durability), water collection tray in PVC-U and carriage housing in polystyrene.	



## PRESSALIT.

Product	SCT 2000 shower change table, coated mesh cover, electrically height adjustable		
Item number	R8571218000		
Ergonomy	The 2000 series shower and changing tables has a low start position, to make transfers to the bench easier. The washable, perforated mesh cover lets the water pass through to the water collection tray underneath.  The flexibility of the shower and changing table provides for optimal working conditions for the carer as well as a high level of comfort and safety for the user.		
Features	A water collection tray with integrated water outlet prevents water from splashing on carers or the floor. The flexible hose attached to the centre mounted outlet of the water collection tray, can be connected to either an outlet in the floor or on the wall. The integrated gas cylinders enable the table to be folded out of the way when not in use to maximise floor space in front of the unit.  Electric with wired hand control – the red buttons clearly indicate "Up" and "Down". The wired hand control comes with a holder for fitting to the wall.  The stretcher of the table is very easy to clean, and the stretcher cover can be unzipped for washing or easy replacement.		
Mains connection (V)	230		
Actuator (motor)	LA40 Careline (Linak), 4000 N, IPX6		
Control box	CA63 Careline, (Linak), IPX6		
Wired remote control	HB30 (Linak), IP66		
Power consumption (maximum load)	Power consumption by maximum load, watt: 420 W Power consumption by standby: 0,5 W		
Warranty	Pressalit makes a commitment to remedy material and manufacturing defects for a period of three years from the invoicing date. NOTICE If the product is placed in an atmosphere heavy in salt or chloride, the warranty will be reduced from the normal 3 years to 1 year. Salt and chloride have a corrosive effect on the products components and will cause a decrease in the life expectancy of the product.		



# PRESSALIT.®

Product	SCT 2000 shower change table, coated mesh cover, electrically height adjustable
Item number	R8571218000
Cleaning	SCT 1000 & 2000 The product is to be cleaned with hot water or a mild soapy cleaning agent. Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged.  The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container.
	DISINFECTANTS: Clinimax Difficil-S Erisan OXY+ Sprit (husholdningssprit) Suma Bac D10 Virkon Rodalon Desinfektionsspray Lysoformin Spezial CaviCide Sufanios Premium Tvättsprit 70% Accel PREVention Wipes Lingettes OxiGenesis from ENVIROX
	NON-DISINFECTANTS: Suma Star free D1 Taski 100 Taski 200 Milizid Citro  The product must be wiped down with a soft rag wrung out in clear water immediately after cleaning, as some materials may otherwise be discolored and stained, and the
Declaration of conformity	surface coating may deteriorate.  CE UK MDR-MASK-RoHS This product is in compliance with all relevant requirements of:  Regulation (EU) 2017/745 on medical devices  Council Directive 2006/42/EC on machinery  Council Directive 2011/65/EC on RoHS. For the UK:  Medical Device Regulation (MDR) 2002 on medical devices.  Supply of Machinery (Safety) Regulations 2008  Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012.



## PRESSALIT®

Item number

SCT 2000 shower change table, coated mesh cover, electrically height adjustable

R8571218000

#### Installation in different wall types

Concrete >B25  V8608 - Mounting kit, 6 coach screws Ø10 x 70 - plugs SX12.  To be ordered separately.	
Solid Brick >= Mz12  V8608 - Mounting kit, 6 coach screws Ø10 x 70 - plugs SX12.  To be ordered separately.	
Solid Sand Lime Brick >= HIz12  V8608 - Mounting kit, 6 coach screws Ø10 x 70 - plugs SX12.  To be ordered separately.	
Aerated Concrete P4  V8658 - Mounting kit, 6 coach screws Ø10 x 70 - plugs GB14.  To be ordered separately.	
Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood  V8608 - Mounting kit, 6 coach screws Ø10 x 70 - plugs SX12. NB! Plugs are not needed.  To be ordered separately.	



#### PRESSALIT®

Product Item number	SCT 2000 shower change table, coated mesh cover, electrically height adjustable R8571218000
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood  Wall fasteners (6 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (2 mm)  Wall fasteners (6 pcs) must be bought separately, for drywall it is possible to use e.g. fischer KD8 toggles or similar.
	Drywall (2 x 12,5 mm) water-resistant  Mounting in this wall type is not recommended - risk of fatal injury to persons and walls.

It is the responsibility of the installer to ensure that suitable wall fasteners are used.

pressalit.com

Pressalit A/S Pressalitvej 1 DK-8680 Ry Tel.: +45 8788 8788 Fax: +45 8788 8789 E-mail: pressalit@pressalit.com

PRESSALIT.