

Product Item number	INDIVO lift for countertop 23.6" - 39.4" RK1810202			
	EAN: 5708590379012			
Color	Gray (RAL 9006)			
Product description	The name INDIVO relates to the individual configuration of the products. Lifts are available for countertops of any length between 23.6" and 111.8".			
	INDIVO lift for countertop, with two motors and control box. Max. load: 220 lbs including the countertop. Incl. cross brace and two brackets. Height adjustable up to 11.8" with switch or wired remote control. For countertop length 23.6" - 39.4". Please indicate length and depth of counter when ordering. Excl. mounting kit.			
Adjustability	Height adjustable			
Adjustment height	11,82 inch			
Product capacity	Maximum load: 220 lbs, this includes the weight of the countertop. The load must be evenly distributed.			
Speed up	Speed up: 0,79 inch/s Speed down: 0,79 inch/s			
Noise level	45 dB			
Materials	Lifting columns: Powder-coated steel Cross brace: Aluminium Brackets: Powder-coated steel			
Ergonomy	An electric height-adjustable kitchen countertop is ideal in all situations where variou users - both seated and standing - use the same kitchen. This is equally true in private homes as well as larger centers with common kitchen facilities such as group homes and care centers.			



Product	INDIVO lift for countertop 23.6" - 39.4"		
Item number	RK1810202		
Features	Lifts are height adjusted either via switches in the front edge or with a wired remot control.		
Actuator (motor)	DL17 Deskline (Linak) 70N, IP22		
Control box	CBD6S (Linak) IP22		
Wired remote control	HB53 (Linak), IPX1		
Power consumption (maximum load)	Power consumption by maximum load: 300 W Power consumption by standby: 2 W		
Warranty	Pressalit makes a commitment to remedy material and manufacturing defects for a period of three years from the invoicing date.		



Product	INDIVO lift for countertop 23.6" - 39.4"
Item number	RK1810202
Cleaning	This product should be cleaned with hot water or a mild cleaning solution. Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged. The following cleaning agents have been tested by Pressalit and may be used, as
	long as they are diluted according to the instructions on the container. DISINFECTANTS: Clinimax Difficil-S Erisan OXY+ Sprit (husholdningssprit) Suma Bac D10 Virkon Rodalon Desinfektionsspray Lysoformin Spezial CaviCide Sufanios Premium Tvättsprit 70%
	NON-DISINFECTANTS: Suma Star free D1 Taski 100 Taski 200 Milizid Citro The product must be wiped down with a soft rag wrung out in clear water immediately after cleaning, as some materials may otherwise be discolored and stained, and the surface coating may deteriorate.
Declaration of	DECALCIFICATION OF ALUMINUM PARTS: Pressalit recommends that water deposits (Calcium, lime etc.) be removed from wall tracks and other aluminum parts using a solution of three parts of 30% acetic acid to seven parts tap water. When the aluminum parts have been washed down with this solution, the parts should be wiped over with a damp cloth wrung out in plain water. This product is solely intended for the US and Canada, and has no EU declaration of
conformity	conformity.



PRESSALIT®

Product		
Item number		

INDIVO lift for countertop 23.6" - 39.4"

RK1810202

Mounting in different wall types

Mounting in different wall types				
	Concrete >B25 V8608 - Mounting kit, 6 lag bolts Ø10 x 70 - plugs SX12. To be ordered separately.			
	Solid Brick >= Mz12 V8608 - Mounting kit, 6 lag bolts Ø10 x 70 - plugs SX12. To be ordered separately.			
	Solid Sand Lime Brick >= HIz12 V8608 - Mounting kit, 6 lag bolts Ø10 x 70 - plugs SX12. To be ordered separately.			
	Aerated Concrete P4 V8658 - Mounting kit, 6 lag bolts Ø10 x 70 - plugs GB14. To be ordered separately.			
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood V8608 - Mounting kit, 6 lag bolts Ø10 x 70 - plugs SX12. NB! Plugs are not needed. To be ordered separately.			



PRESSALIT®

Product Item number	INDIVO lift for countertop 23.6" - 39.4" RK1810202	
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood Wall fasteners (6 pcs) must be bought separately, for drywall it is possible to use e.g. SnapTight or WingIt anchors or similar.	
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (.08 inch) Wall fasteners (6 pcs) must be bought separately, for drywall it is possible to use e.g. SnapTight or WingIt anchors or similar.	
	Drywall (2 x 12,5 mm) water-resistant Wall fasteners (6 pcs) must be bought separately, for drywall it is possible to use e.g. SnapTight or WingIt anchors or similar.	

It is the responsibility of the installer to ensure that suitable wall fasteners are used.

pressalit.com

Pressalit A/S
Pressalitvej 1
DK-8680 Ry
Tel.: +45 8788 8788
Fax: +45 8788 8789
E-mail: pressalit@pressalit.com