

| Product | INDIVO lift for wall cupboards 400-1200 mm | | |
|---------------------|---|---|--|
| Item number | RK1220 | | |
| | EAN:5708590378541 | 400 - 1200 | |
| Product description | The name INDIVO relates to the individua INDIVO lift for wall cupboards, with one m Height adjustable 430 mm with switches of adjusting downward, the lift will also move For wall cupboards width 400-1200 mm. F wall cupboards when ordering. Excl. mounting kit. | otor and control box. or wired remote control. When height a 180 mm towards the user. | |
| Adjustability | Height adjustable | | |
| Adjustment height | 430 mm | | |
| Product capacity | Max. load (including cupboards): 1 lift: 110 kg | | |
| Speed upwards | Speed up mm: 18 mm/s Speed down mm: 18 mm/s | | |
| Noise level | 48 dB | | |
| Materials | Material: Lift motor: Steel Cross braces: Aluminium Switches: ABS plastic | | |
| Ergonomy | Wall cupboards are moved diagonally, that is both vertically and towards the user. This makes it easy for seated users and children to see and access covered contents. Height-adjustable wall cupboards provide extra storage options in kitchens where cupboards cannot be installed under worktops out of consideration for seated users | | |



| Product Item number | INDIVO lift for wall cupboards 400-1200 mm RK1220 | |
|----------------------------------|--|--|
| Features | Lift heights for wall cupboards are adjusted via switches in the front worktop edge. Operating switches can be placed wherever you want along the front edge. The switches are colour-coded - aluminium to operate worktops, and red to operate wall cupboards. The design of the lifts ensures that the lift motors are as discreet as possible, regardless of the cupboard position. When the wall cupboards are lowered 430 mm to their lowest position, they are also extended 180 mm towards the user. | |
| Actuator (motor) | LA31 Deskline (Linak), 1500N, IPX1 | |
| Control box | CBD6 (Linak) | |
| Wired remote control | HB53 (Linak), IPX1 | |
| Power consumption (maximum load) | Power consumption by maximum load, watt: 187 W Power consumption by standby: 1,5 W | |
| Warranty | Pressalit makes a commitment to remedy material and manufacturing defects for a period of three years from the invoicing date. | |



| Product Item number | INDIVO lift for wall cupboards 400-1200 mm RK1220 | |
|---------------------------|---|--|
| Cleaning | INDIVO lift for kitchenwall cupboard. The product is to be cleaned with hot water or a mild soapy cleaning agent. Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged. | |
| | The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container. | |
| | DISINFECTANTS: Clinimax Difficil-S Erisan OXY+ | |
| | NON-DISINFECTANTS: Suma Star free D1 Taski 100 Taski 200 | |
| | The product must be wiped down with a soft rag wrung out in clear water immediately after cleaning, as some materials may otherwise be discolored and stained, and the surface coating may deteriorate. | |
| | DECALCIFICATION OF ALUMINUM PARTS: Pressalit recommends that chalky deposits be removed from wall tracks and other aluminum parts using a solution of three parts 30% acetic acid to seven parts tap water. When the aluminum parts have been washed down with this solution, the parts must be wiped over with a damp cloth wrung out in clear water. | |
| Declaration of conformity | CE UK RoHS_LVD_EMC This product is in compliance with relevant requirements in: - the RoHS Directive 2011/65/EU - the EMC Directive 2014/30/EU - the Low Voltage Directive 2014/35/EU. Furthermore, for the UK, in compliance with relevant requirements in: - The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012 - The Electromagnetic Compatibility Regulations 2016 - The Electrical Equipment (Safety) Regulations 2016 | |



Product Item number INDIVO lift for wall cupboards 400-1200 mm RK1220

pressalit.com

Pressalit A/S Pressalitvej 1 DK-8680 Ry Tel.: +45 8788 8788 Fax: +45 8788 8789 E-mail: pressalit@pressalit.com

