

PRESSALIT.

Pressalit Chilli 1110 Toilet seat with soft close, incl. universal hinge in stainless steel

Features Soft close

 Item number
 1110000-DK4999

 EAN:5708590382494

Pressalit Chilli is a stable toilet seat that fits many different toilet bowls. With its excellent stability, its timeless design, and its noiseless soft close function, this

toilet seat is a safe choice for your toilet

Colour White

Description


PRESSALIT toilet seat with cover, model "Pressalit
Chilli", art. no. 1110 made of colour ingrained duroplast
with built-in soft close function, incl. DK4 universal

hinge in stainless steel.

- centre distance: 90-170 mm

- load - ring seat 240 kg

- 10 year guarantee





Design typeSandwichDesignerPressalit

Design year 2020



PRESSALIT.

Pressalit Chilli 1110
Toilet seat with soft close, incl. universal hinge in stainless steel

Materials TOILET SEAT:

The material is colour ingrained duroplast (UF A 10 = urea formaldehyde) that contains no environmentally hazardous substances. UF plastic comprises 67% urea formaldehyde resin, 28% cellulose, as well as 5% minerals, pigments, lubricants and moisture content. The raw material from the supplier contains up to 0.03% free formaldehyde and even less following curing.

POLYGIENE (only relevant for toilet seats with polygiene):

Polygiene consists of biocide silver chloride, which has an anti-bacterial effect. This is why the bacteria growth is hampered 24 hours a day.

BUFFERS:

EVA (copolymer made of ethylene and vinyl acetate).

DAMPER KIT (only relevant for toilet seats with soft close):

Hydraulic damper with stainless steel damper casing and thermoplastic parts.

MOUNT/HINGES:

Stainless steel model W. no. 1.4301/M and thermoplastic.

Product capacity Load - ring seat 240 kg

Weight 2,11 kg

Carton size 488x388x72 mm

Gross weight 2,43 kg

Crate size 500x400x368 mm

Weight per crate 12,15 kg

Qty per crate 5

Crates per pallet 18

Qty per pallet 90

Cleaning Use a mild soap solution to clean the seat. Please take care that the seat and hinges are

not left damp. Dry off any residual water or cleaning agent with a soft cloth. Avoid contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make sure that the seat and cover are kept in an upright position until all cleaning agent has

been flushed away.



PRESSALIT.

Pressalit Chilli 1110
Toilet seat with soft close, incl. universal hinge in stainless steel

Warranty

Your Pressalit toilet seat is subject to a 10-year product warranty against presentation of receipt. You should contact the dealer or store where you purchased the seat in the event of a complaint.

| Strict | Stri

Subject to changes in the product range, technical changes and printing errors.

pressalit.com

Pressalit A/S Pressalitvej 1 DK-8680 Ry Tel.: +45 8788 8788 Fax: +45 8788 8789 E-mail: pressalit@pressalit.com

PRESSALIT: