

## PRESSALIT.

shower and changing tables of high quality. They are designed to provide a stab platform for showering and changing adults and children with reduced mobility. These tables can be used in schools, institutions, hospitals and private homes are all designed to be durable, comfortable and easy to clean. The design and flexibility of the tables ensures optimal working conditions for the carer as well as a high level of comfort and safety for the user.  MCT 3 change trolley, 700 x 1900 mm, two fold-down sides. Electrically height adjustable with wired remote control. 500 mm lifting range, from 450 to 950 mm.  Mattress to be ordered separately.  Adjustability  Height adjustable  Adjustment height  Maximum user weight (MUM): 200 kg. Maximum load (SWL): 205 kg. This product has been tested statically with a load of 512,5 kg as the IEC 60601 standard requires testing with safety factor 2.5.  Speed upwards  Speed up mm: 17 mm/s Speed down mm: 17 mm/s Speed down mm: 17 mm/s	Product	MCT 3 change trolley, electrically height adjustable
Product description  Pressalit offers a variety of mobile and wall-hung, height-adjustable and fixed he shower and changing tables of high quality. They are designed to provide a stab platform for showering and changing adults and children with reduced mobility. These tables can be used in schools, institutions, hospitals and private homes at are all designed to be durable, comfortable and easy to clean. The design and flexibility of the tables ensures optimal working conditions for the carer as well as a high level of comfort and safety for the user.  MCT 3 change trolley, 700 x 1900 mm, two fold-down sides. Electrically height adjustable with wired remote control. 500 mm lifting range, from 450 to 950 mm.  Mattress to be ordered separately.  Adjustability  Adjustability  Height adjustable  Adjustment height  Maximum load (SWL): 200 kg.  Maximum load (SWL): 205 kg.  This product has been tested statically with a load of 512,5 kg as the IEC 60601 standard requires testing with safety factor 2.5.  Speed upwards  Speed down mm: 17 mm/s  Speed down mm: 17 mm/s  Speed down mm: 17 mm/s	Item number	R9652719000
shower and changing tables of high quality. They are designed to provide a stab platform for showering and changing adults and children with reduced mobility. These tables can be used in schools, institutions, hospitals and private homes at are all designed to be durable, comfortable and easy to clean. The design and flexibility of the tables ensures optimal working conditions for the carer as well as a high level of comfort and safety for the user.  MCT 3 change trolley, 700 x 1900 mm, two fold-down sides. Electrically height adjustable with wired remote control. 500 mm lifting range, from 450 to 950 mm.  Mattress to be ordered separately.  Adjustability  Height adjustable  Froduct capacity  Maximum user weight (MUM): 200 kg. Maximum load (SWL): 205 kg. This product has been tested statically with a load of 512,5 kg as the IEC 60601 standard requires testing with safety factor 2.5.  Speed upwards  Speed up mm: 17 mm/s Speed down mm: 17 mm/s Speed down mm: 17 mm/s	Colour	EAN:5708590389967
Adjustment height  Froduct capacity  Maximum user weight (MUM): 200 kg. Maximum load (SWL): 205 kg. This product has been tested statically with a load of 512,5 kg as the IEC 60601- standard requires testing with safety factor 2.5.  Speed upwards  Speed up mm: 17 mm/s Speed down mm: 17 mm/s  Noise level  50 dB	Product description	These tables can be used in schools, institutions, hospitals and private homes and are all designed to be durable, comfortable and easy to clean.  The design and flexibility of the tables ensures optimal working conditions for the carer as well as a high level of comfort and safety for the user.  MCT 3 change trolley, 700 x 1900 mm, two fold-down sides.  Electrically height adjustable with wired remote control.  500 mm lifting range, from 450 to 950 mm.
Product capacity  Maximum user weight (MUM): 200 kg. Maximum load (SWL): 205 kg. This product has been tested statically with a load of 512,5 kg as the IEC 60601- standard requires testing with safety factor 2.5.  Speed upwards  Speed up mm: 17 mm/s Speed down mm: 17 mm/s  Noise level  50 dB	Adjustability	Height adjustable
Maximum load (SWL): 205 kg.  This product has been tested statically with a load of 512,5 kg as the IEC 60601 standard requires testing with safety factor 2.5.  Speed upwards  Speed up mm: 17 mm/s Speed down mm: 17 mm/s  Speed down mm: 50 dB	Adjustment height	500 mm
Noise level 50 dB	Product capacity	Maximum load (SWL): 205 kg.  This product has been tested statically with a load of 512,5 kg as the IEC 60601-1
	Speed upwards	
Metaviele	Noise level	50 dB
Plastics, compact laminate and powder-lacquered steel.	Materials	Plastics, compact laminate and powder-lacquered steel.



## PRESSALIT.

Product Item number	MCT 3 change trolley, electrically height adjustable R9652719000
Ergonomy	<ul> <li>The ergonomically designed safety rails have a practical lower central section, which provides better access and work environment for the carer while transferring, changing and dressing the user.</li> </ul>
	<ul> <li>One hand operated safety rails allows the carer to maintain eye contact as well as physical contact with the user during the whole process, the foldable safety rails also provide easy access from all four sides of the table.</li> </ul>
	<ul> <li>The cut-out grips in the safety rails enable users to assist when being turned, which motivates physical training.</li> </ul>
	Easy to clean, smooth contact surfaces which do not collect dirt and bacteria.
Features	The trolley can be moved from room to room for easy transport and multiple users.
Mains connection (V)	<ul> <li>Intuitive, easy-to-use drop down rails with one hand operation.</li> <li>230</li> </ul>
Actuator (motor)	LA40 (Linak) IPX6
Control box	CA30 (Linak) IPX6
Wired remote control	HB30 (Linak) IPX6
Power consumption (maximum load)	Power consumption by maximum load, watt: 330 W Power consumption by standby: 0,5 W
Warranty	Pressalit makes a commitment to remedy material and manufacturing defects for a period of three years from the invoicing date. NOTICE If the product is placed in an atmosphere heavy in salt or chloride, the warranty will be reduced from the normal 3 years to 1 year. Salt and chloride have a corrosive effect on the products components and will cause a decrease in the life expectancy of the product.



## PRESSALIT®

Product	MCT 3 change trolley, electrically height adjustable
Item number	R9652719000
Cleaning	MSCT 1, MCT 2+3 The product is to be cleaned with hot water or a mild soapy cleaning agent. Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged.  The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container.  DISINFECTANTS: Clinimax Difficil-S Erisan OXY+ Sprit (husholdningssprit) Suma Bac D10 Virkon Rodalon Desinfektionsspray Lysoformin Spezial CaviCide Sufanios Premium Tvättsprit 70% Accel PREVention Wipes Lingettes
	NON-DISINFECTANTS: Suma Star free D1 Taski 100 Taski 200 Millizid Citro  The product must be wiped down with a soft rag wrung out in clear water immediately
Declaration of conformity	after cleaning, as some materials may otherwise be discolored and stained, and the surface coating may deteriorate.  UK MDR-MASK-RoHS This product is in compliance with all relevant requirements of:  - Medical Device Regulation (MDR) 2002 on medical devices.  - Supply of Machinery (Safety) Regulations 2008  - Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012.



## PRESSALIT®

Product MCT 3 change trolley, electrically height adjustable

R9652719000

pressalit.com

Pressalit A/S
Pressalitvej 1
DK-8680 Ry
Tel.: +45 8788 8788
Fax: +45 8788 8789
E-mail: pressalit@pressalit.com