



Pressalit 3 684
Toilet seat with soft close incl. hinge in stainless steel.

Features

Lift-off, Soft close

Item number

684000-D77999
VVS:615022000
NRF:6190122
RSK:7904470
EAN:5708590300481

With Pressalit 3 we grant our customers the opportunity to elegantly combine quality, design and functionality. Pressalit 3 goes perfectly with the Philippe Starck 3 series from Duravit. The seat has a discreet, stylish and minimalistic design that perfectly complements the clean lines of the Starck 3 bowl.






Colour

White

Description

PRESSALIT toilet seat with cover, model "Pressalit 3", art. no. 684 made of colour ingrained duroplast with D77 uniflex hinge of stainless steel.

- centre distance: 270 - 320 mm
- load - ring seat 240 kg
- suitable for Philippe Starck 3 (Duravit)
- 10 year guarantee



Design type

Wrap-over

Designer

Pressalit

Design year

2009



Pressalit 3 684
Toilet seat with soft close incl. hinge in stainless steel.

Materials

TOILET SEAT:

The material is colour ingrained duroplast (UF A 10 = urea formaldehyde) that contains no environmentally hazardous substances. UF plastic comprises 67% urea formaldehyde resin, 28% cellulose, as well as 5% minerals, pigments, lubricants and moisture content. The raw material from the supplier contains up to 0.03% free formaldehyde and even less following curing.

BUFFERS:

EVA (copolymer made of ethylene and vinyl acetate).

DAMPER KIT (only relevant for toilet seats with soft close):

Hydraulic damper with stainless steel damper casing and thermoplastic parts.

MOUNT/HINGES:

Stainless steel model W. no. 1.4301/M and thermoplastic.

Product capacity

Load - ring seat 240 kg

Weight

2,735 kg

Carton size

488x388x72 mm

Gross weight

3,152 kg

Crate size

500x400x368 mm

Weight per crate

15,76 kg

Qty per crate

5

Crates per pallet

20

Qty per pallet

100

Cleaning

Use a mild soap solution to clean the seat. Please take care that the seat and hinges are not left damp. Dry off any residual water or cleaning agent with a soft cloth. Avoid contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make sure that the seat and cover are kept in an upright position until all cleaning agent has been flushed away.



PRESSALIT®

Pressalit 3 684
Toilet seat with soft close incl. hinge in stainless steel.

Warranty

Your Pressalit toilet seat is subject to a 10-year product warranty against presentation of receipt. You should contact the dealer or store where you purchased the seat in the event of a complaint. In the event of complaints about defective materials and/or manufacturing defects and/or functional limitations ascertained within a 10-year period, following proper use and cleaning of the toilet seat (we reserve the right to examine the toilet seat at our factory), Pressalit will deliver spare parts or replace the toilet seat by an identical or similar model. If the color is no longer available, Pressalit reserves its right to replace the toilet seat by a similar model in the color white. Upon replacement or delivery of a spare part, the warranty period will not be extended nor renewed. If replacement is not possible, Pressalit may instead refund the purchase price.

Subject to changes in the product range, technical changes and printing errors.

pressalit.com
