

PRESSALIT.

Pressalit 3 684

Toilet seat with soft close incl. hinge in stainless steel.

Features Soft close

Item number 684001-D38999

EAN:5708590292311

With Pressalit 3 we grant our customers the opportunity to elegantly combine quality, design and functionality. Pressalit 3 goes perfectly with the Philippe Starck 3 series from Duravit. The seat has a discreet, stylish and minimalistic design that perfectly complements the clean

lines of the Starck 3 bowl.

Colour Black (RAL 9005)

DescriptionPRESSALIT toilet seat with cover, model "Pressalit 3", art. no. 684 made of colour ingrained duroplast with


D38 uniflex hinge of stainless steel.

- centre distance: 270 - 320 mm


- load - ring seat 240 kg

- suitable for Philippe Starck 3 (Duravit)

- 10 year guarantee







Design type Wrap-over

Designer Pressalit

Design year 2009



PRESSALIT.

Pressalit 3 684

Toilet seat with soft close incl. hinge in stainless steel.

TOILET SEAT: Materials

The material is colour ingrained duroplast (UF A 10 = urea formaldehyde) that contains no environmentally hazardous substances. UF plastic comprises 67% urea formaldehyde resin, 28% cellulose, as well as 5% minerals, pigments, lubricants and moisture content. The raw material from the supplier contains up to 0.03% free

formaldehyde and even less following curing.

BUFFERS:

EVA (copolymer made of ethylene and vinyl acetate).

DAMPER KIT (only relevant for toilet seats with soft close):

Hydraulic damper with stainless steel damper casing and thermoplastic parts.

MOUNT/HINGES:

Stainless steel model W. no. 1.4301/M and thermoplastic.

Product capacity Load - ring seat 240 kg

Weight 2,865 kg

Carton size 488x388x72 mm

Gross weight 3,282 kg

500x400x368 mm Crate size

Weight per crate 16,41 kg

5 Qty per crate

Crates per pallet 20

Qty per pallet 100

Cleaning Use a mild soap solution to clean the seat. Please take care that the seat and hinges are not left damp. Dry off any residual water or cleaning agent with a soft cloth. Avoid

contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make sure that the seat and cover are kept in an upright position until all cleaning agent has

been flushed away.



PRESSALIT.

Pressalit 3 684
Toilet seat with soft close incl. hinge in stainless steel.

Warranty

Your Pressalit toilet seat is subject to a 10-year product warranty against presentation of receipt. You should contact the dealer or store where you purchased the seat in the event of a complaint.

| Strict | Stri

Subject to changes in the product range, technical changes and printing errors.

pressalit.com

Pressalit A/S Pressalitvej 1 DK-8680 Ry Tel.: +45 8788 8788 Fax: +45 8788 8789 E-mail: pressalit@pressalit.com

PRESSALIT: