

-

_

PRESSALIT.

Pressalit 720 Toilet seat with soft close incl. hinge in stainless steel

Features	Soft close
Item number	720000-D75999 EAN:5708590298160
	Pressalit 720 is a D-shaped toilet seat with gorgeous wrap-over and soft close. Particularly suited to building projects.
Colour	White
Description	PRESSALIT toilet seat with cover, model "Pressalit 720", art. no. 720 made of colour ingrained duroplast with D74 universal hinge in stainless steel. - centre distance: 115-195 mm - load - ring seat 180 kg - suitable for many universal D-shaped toilets - 10 year guarantee $\int \frac{130 - 180}{\sqrt{405} + 236} \int \frac{49173}{\sqrt{109} + \sqrt{109}} \int \frac{49173}{\sqrt{109} + \sqrt{109} + \sqrt{100}} \int \frac{4003}{\sqrt{100} + \sqrt{100} + \sqrt{100}} \int \frac{4003}{\sqrt{100} + \sqrt{100} + 1$
Design type	Wrap-over
Designer	Pressalit
Design year	2011
Materials	TOILET SEAT: The material is colour ingrained duroplast (UF A 10 = urea formaldehyde) that contains no environmentally hazardous substances. UF plastic comprises 67% urea formaldehyde resin, 28% cellulose, as well as 5% minerals, pigments, lubricants and moisture content. The raw material from the supplier contains up to 0.03% free formaldehyde and even less following curing.
	BUFFERS: EVA (copolymer made of ethylene and vinyl acetate).
	DAMPER KIT (only relevant for toilet seats with soft close): Hydraulic damper with stainless steel damper casing and thermoplastic parts.
	MOUNT/HINGES: Stainless steel model W. no. 1.4301/M and thermoplastic.



PRESSALIT.

Pressalit 720 Toilet seat with soft close incl. hinge in stainless steel

Product capacity	
Weight	2,31 kg
Carton size	488x388x72 mm
Gross weight	2,774 kg
Crate size	500x400x368 mm
Weight per crate	13,87 kg
Qty per crate	5
Crates per pallet	18
Qty per pallet	90
Cleaning	Use a mild soap solution to clean the seat. Please take care that the seat and hinges are not left damp. Dry off any residual water or cleaning agent with a soft cloth. Avoid contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make sure that the seat and cover are kept in an upright position until all cleaning agent has been flushed away.
Warranty	Your Pressalit toilet seat is subject to a 10-year product warranty against presentation of receipt. You should contact the dealer or store where you purchased the seat in the event of a complaint. In the event of complaints about defective materials and/or manufacturing defects and/or functional limitations ascertained within a 10-year period, following proper use and cleaning of the toilet seat (we reserve the right to examine the toilet seat at our factory), Pressalit will deliver spare parts or replace the toilet seat by an identical or similar model. If the color is no longer available, Pressalit reserves its right to replace the toilet seat by a similar model in the color white. Upon replacement or delivery of a spare part, the warranty period will not be extended nor renewed. If replacement is not possible, Pressalit may instead refund the purchase price.
	Subject to changes in the product range, technical changes and printing errors.
	•

pressalit.com

Pressalit A/S Pressalitvej 1 DK-8680 Ry Tel.: +45 8788 8788 Fax: +45 8788 8789 E-mail: pressalit@pressalit.com

